

QUALITATIVE BEHAVIOUR OF NUMERICAL TRAVELING SOLUTIONS FOR REACTION-DIFFUSION EQUATIONS WITH MEMORY

A. ARAÚJO, J.A. FERREIRA AND P. OLIVEIRA

ABSTRACT: In this paper the qualitative properties of numerical traveling wave solutions for integro-differential equations, which generalize the well known Fisher equation are studied. The integro-differential equation is replaced by an equivalent hyperbolic equation which allows us to characterize the numerical velocity of traveling wave solutions. Numerical results are presented.

KEYWORDS: Fisher equation, integro-differential equation, traveling wave solution, numerical approximation.

AMS SUBJECT CLASSIFICATION (2000): 65M06, 65M20, 65M15.

1. Reaction-diffusion equations with memory

Mathematical models based on the well known Fisher reaction-diffusion equation

$$\frac{\partial u}{\partial t} = D \frac{\partial^2 u}{\partial x^2} + f(u), \quad (x, t) \in \mathbb{R} \times \mathbb{R}^+, \quad (1)$$

have been largely used to describe physical, chemical or biological models ([3], [4],[6]). We can mention for example models of propagation of a vortex front in an unstable fluid-flow, models of agregation and deposition, ecological models or biological invasions models. In (1) D is a diffusion coefficient, f is a nonlinear function with $f(u) > 0$ and $f(0) = f(1) = 0$.

Fisher equations present however two unphysical properties which are related. Firstly, due to its parabolic character, if a sudden change occurs at a certain point it will be felt instantly everywhere, though with exponentially small amplitudes at distant points. The second unphysical property concerns the overestimation of the velocity of traveling waves. In fact for a sufficiently localized initial condition, the solution of (1) converges to a traveling wave solution in the long time limit ([1],[6]) connecting the two steady states: $u = 0$ (unstable) and $u = 1$ (stable). This means that, a

Received September 2, 2004.

This work has been supported by Centro de Matemática da Universidade de Coimbra and Project POCTI/35039/MAT/2000

solution of type $\psi(x - ct)$ – where ψ is a monotonically decreasing function such that $\psi(-\infty) = 1$, $\psi(+\infty) = 0$, and c is the velocity at which the wave profile ψ moves – will describe the evolution of the system between the two steady states. In several models the reaction term is represented by $f(u) = U(1 - u)u$ where U stands for a reaction rate parameter. In this case it is well known ([6]) that the velocity c_F of the traveling wave is equal to $\sqrt{4DU}$. When the chemical rate becomes very fast arbitrarily large unphysical velocities arise which contradicts the simple fact that they should not exceed the propagation rate of the real transport process.

To overcome these unphysical properties the flux q_F used in (1) and defined by Fick's law

$$q_F = -D \frac{\partial u}{\partial x},$$

can be replaced by a flux with memory defined by

$$q_I = -\frac{D}{\tau} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial u}{\partial x}(x, s) ds, \quad (2)$$

where τ is a relaxation parameter ([3]–[5]). Using (2), the mathematical models based on the parabolic Fisher equation are then replaced by the integro-differential equation

$$\frac{\partial u}{\partial t} = \frac{D}{\tau} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial^2 u}{\partial x^2}(x, s) ds + f(u), \quad (x, t) \in \mathbb{R} \times \mathbb{R}^+. \quad (3)$$

The integro-differential equation (3), which leads to the Fisher equation when τ converges to zero, is known as a generalized Fisher-Kolmogorov-Petrovski-Piskunov equation (FKPP) and is considered, for instance, in [3]–[5]. Integro-differential equations of type (3) have been also considered in [2], [10], [11].

The computation of the velocity c_I of a traveling wave solution of (3) has attracted considerable interest in the past years (see, for instance, [3]–[5], [8]). Considering an initial condition of Heaviside type the authors established in [3] that

$$c_I = \frac{\sqrt{4DU}}{1 + \tau U}, \quad (4)$$

with $f(u) = Uu(1 - u)$, where U is a constant and $\tau U \leq 1$. This result was generalized in [4] for a reaction term of type $f(u) = U(x)u(1 - u)$. The overestimation of c_F is corrected by flux (2) because $c_I \leq c_F$. We remark that

considering c_I as a function of U and τ , in the domain defined by $\tau U \leq 1$, we can easily establish that $c_I \leq \sqrt{D}\tau$, where this maximum is attained for $U\tau = 1$.

In the present paper we are concerned with the construction of numerical methods to solve (3) which present accurate numerical velocities. One possible approach is the use of finite differences for the discretization of partial derivatives and quadrature formulas for the the integral term. This method was considered for instance in [2], [10]. Another approach is the use of Galerkin method (see, for instance, [11] and the references cited there). The method proposed in this paper avoids the discretization of the integral term and is based on the discretization of a partial differential equation equivalent to (3): the telegraph equation

$$\frac{\partial^2 u}{\partial t^2} + \frac{\partial u}{\partial t} \left(\frac{1}{\tau} - f'(u) \right) = \frac{D}{\tau} \frac{\partial^2 u}{\partial x^2} + \frac{1}{\tau} f(u). \quad (5)$$

In Section 2 we establish, under certain conditions, the equivalence between the integro-differential equation (3) and the telegraph equation, and we study the sensitivity of the models relatively to initial conditions. In Section 3 we study the behaviour of two simple numerical methods for solving the integro-differential equation (3) obtained considering the discretization of the equivalent telegraph equation. The numerical speeds of the methods are studied. Numerical simulations are included.

2. The generalized FKPP equation versus the telegraph equation

In this section we prove the equivalence between the integro-differential equation (3) and a partial differential equation of second order in time – the telegraph equation. We note that, to describe reaction-diffusion processes, several authors ([7], [8]) have used the telegraph equation. The sensitivity of the integro-differential equation relatively to the initial conditions is also established in what follows.

If $f \in C^1$, we have, from (3),

$$\frac{\partial^2 u}{\partial t^2}(x, t) = \frac{D}{\tau} \frac{\partial^2 u}{\partial x^2}(x, t) - \frac{D}{\tau^2} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial^2 u}{\partial x^2}(x, s) ds + f'(u) \frac{\partial u}{\partial t} \quad (6)$$

and consequently we obtain (5). If (3) is coupled with the initial condition

$$u(x, 0) = u_0(x), \quad x \in \mathbb{R}, \quad (7)$$

then for the telegraph equation (5) we have the following initial conditions:

$$\begin{cases} u(x, 0) = u_0(x), x \in \mathbb{R}, \\ \frac{\partial u}{\partial t}(x, 0) = f(u_0(x)), x \in \mathbb{R}. \end{cases} \quad (8)$$

Inversely, if u is a solution of the telegraph equation (5) with initial conditions

$$\begin{cases} \frac{\partial u}{\partial t}(x, 0) = q(x), x \in \mathbb{R}, \\ u(x, 0) = p(x), x \in \mathbb{R}, \end{cases} \quad (9)$$

then u is a solution of the modified integral equation

$$\frac{\partial u}{\partial t} = \frac{D}{\tau} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial^2 u}{\partial x^2}(x, s) ds + f(u) + (q(x) - f(p(x))) e^{-\frac{t}{\tau}}. \quad (10)$$

In fact (5) is equivalent to

$$\frac{\partial}{\partial t} \left(\frac{\partial u}{\partial t} e^{\frac{t}{\tau}} \right) = \frac{D}{\tau} \frac{\partial^2 u}{\partial x^2} e^{\frac{t}{\tau}} + \frac{\partial}{\partial t} \left(f(u) e^{\frac{t}{\tau}} \right).$$

Integrating this equation we obtain

$$\frac{\partial u}{\partial t} = \frac{D}{\tau} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial^2 u}{\partial x^2} ds + f(u) + e^{-\frac{t}{\tau}} g(x),$$

where $g(x)$ stands for an integration constant. Attending to (9) we finally establish (10).

The modified integral equation (10) coincides with equation (3) if and only if $q(x) = f(p(x))$, $u_0(x) = p(x)$, $x \in \mathbb{R}$.

We summarize the previous considerations in the following result:

Proposition 1. *Let u be a solution of (3) with initial condition (7) and v a solution of (5) with initial conditions (9). Then $u = v$ if and only if $q(x) = f(p(x))$, $p(x) = u_0(x)$, $x \in \mathbb{R}$.* ■

Equation (5) is an hyperbolic equation with characteristics defined by $\frac{dx}{dt} = \pm \sqrt{\frac{D}{\tau}}$. As τ increases, the "memory" of the process also increases. In fact the angular coefficient of the characteristics is a decreasing function

of τ and consequently a greater time interval, $\left[t - x\sqrt{\frac{\tau}{D}}, t + x\sqrt{\frac{\tau}{D}} \right]$, is involved in the computation of $u(x, t)$.




FIGURE 1. Domain of dependence.

As a consequence the first unphysical property of parabolic Fisher equation is obviously corrected by hyperbolic equation (5): a change that occurs at a certain point x will not be felt instantly everywhere, but after an elapsed time of $x\sqrt{\frac{\tau}{D}}$. When $\tau \rightarrow 0$ the two characteristics of the hyperbolic equation degenerate in a only one vertical characteristic.

Another consequence of the hyperbolic character of the telegraph equation is that the total energy associated with (5) satisfies

$$\frac{d}{dt} \left(\left\| \frac{\partial u}{\partial t} \right\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \frac{\partial u}{\partial x} \right\|_{L^2(\mathbb{R})}^2 - \int_{\mathbb{R}} g(u) dx \right) = 2 \int_{\mathbb{R}} \left(\frac{f'(u)\tau - 1}{\tau} \left(\frac{\partial u}{\partial t} \right)^2 \right) d\xi \quad (11)$$

where $g(u) = \frac{1}{2} \int_0^u f(\xi) d\xi$.

If $1 - \tau f'(u) \geq 0$, we obtain from (11)

$$\left\| \frac{\partial u}{\partial t} \right\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \frac{\partial u}{\partial x} \right\|_{L^2(\mathbb{R})}^2 - \int_{\mathbb{R}} g(u) dx \leq \left\| f(u_0) \right\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| u'_0 \right\|_{L^2(\mathbb{R})}^2 - \int_{\mathbb{R}} g(u_0) dx. \quad (12)$$

We now study the sensitivity of the integral equation relatively to the initial conditions.

Proposition 2. *Let u be a solution of (3) with initial condition (7) and v a solution of (10) with initial condition $v(x, 0) = p(x)$. If u_0 and p have*

compact support in \mathbb{R} , then for $w = u - v$ holds the following inequality

$$\begin{aligned} \|w\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial w}{\partial x} ds \right\|_{L^2(\mathbb{R})}^2 &\leq e^{Mt} \|u_0 - p\|_{L^2(\mathbb{R})}^2 \\ &+ \|q - f(p)\|_{L^2(\mathbb{R})}^2 \tau \frac{e^{Mt} - e^{-\frac{t}{\tau}}}{1 + \tau M}, \end{aligned} \quad (13)$$

where $M = \max\{-\frac{2}{\tau}, 2f'_{max} + 1\}$.

Proof: The solution w satisfies the following equation

$$\frac{\partial w}{\partial t} = \frac{D}{\tau} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial^2 w}{\partial x^2}(x, s) ds + f(u) - f(v) - (q(x) - f(p(x))) e^{-\frac{t}{\tau}}.$$

Multiplying by w this last equation with respect to the $L^2(\mathbb{R})$ inner product we obtain

$$\begin{aligned} \frac{1}{2} \frac{d}{dt} \|w\|_{L^2(\mathbb{R})}^2 &= -\frac{D}{\tau} \int_{\mathbb{R}} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial w}{\partial x}(x, s) \frac{\partial w}{\partial x}(x, t) ds dx \\ &+ \int_{\mathbb{R}} (f(u) - f(v))w dx + e^{-\frac{t}{\tau}} \int_{\mathbb{R}} (f(p) - q)w dx. \end{aligned} \quad (14)$$

Using integration by parts it can be established that

$$\begin{aligned} \frac{D}{\tau} \int_{\mathbb{R}} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial w}{\partial x}(x, s) \frac{\partial w}{\partial x}(x, t) ds dx &= \frac{d}{dt} \frac{1}{2} \frac{D}{\tau} \left\| \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial w}{\partial x} ds \right\|_{L^2(\mathbb{R})}^2 \\ &+ \frac{D}{\tau^2} \left\| \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial w}{\partial x} ds \right\|_{L^2(\mathbb{R})}^2. \end{aligned} \quad (15)$$

As the inequalities

$$\int_{\mathbb{R}} (f(u) - f(v))w dx \leq f'_{max} \|w\|_{L^2(\mathbb{R})}^2 \quad (16)$$

and

$$e^{-\frac{t}{\tau}} \int_{\mathbb{R}} (f(p) - q)w dx \leq \frac{1}{2} e^{-\frac{t}{\tau}} \|f(p) - q\|_{L^2(\mathbb{R})}^2 + \frac{1}{2} \|w\|_{L^2(\mathbb{R})}^2 \quad (17)$$

hold, we establish from (14)-(17)

$$\frac{d}{dt} E(w) \leq ME(w) + e^{-\frac{t}{\tau}} \|f(p) - q\|_{L^2(\mathbb{R})}^2, \quad (18)$$

with $M = \max\{-\frac{2}{\tau}, 2f'_{max} + 1\}$ and

$$E(w) = \|w\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial w}{\partial x} ds \right\|_{L^2(\mathbb{R})}^2.$$

Integrating the differential inequality (18) we obtain (13). ■

If $f(u) = 0$ we conclude from (13) that $E(w) \rightarrow 0$ when $t \rightarrow \infty$. If $f(u) \neq 0$ and $f'_{max} > 0$, (13) just establishes that $E(w)$ is bounded for any fixed time T . In the context of loss reaction equations we have $f' < 0$ and consequently estimation (13) allow us to conclude that $E(w)$ is decreasing.

In the following we compare estimate (12) with estimate (13) for the particular choice $f(u) = u$. From (12) we deduce

$$\left\| \frac{\partial u}{\partial t} \right\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \frac{\partial u}{\partial x} \right\|_{L^2(\mathbb{R})}^2 - \|u\|_{L^2(\mathbb{R})}^2 \leq \|f(u_0)\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \|u'_0\|_{L^2(\mathbb{R})}^2 - \frac{1}{\tau} \|u_0\|_{L^2(\mathbb{R})}^2. \quad (19)$$

Otherwise from (13) we obtain

$$\|u\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial u}{\partial x} ds \right\|_{L^2(\mathbb{R})}^2 \leq e^{2t} \|u_0\|_{L^2(\mathbb{R})}^2. \quad (20)$$

Inequality (20) improves the information given by (19). In fact from (20) we obtain an upper bound to the difference between the total energy – kinetic and potential – $\left\| \frac{\partial u}{\partial t} \right\|_{L^2(\mathbb{R})}^2 + \frac{D}{\tau} \left\| \frac{\partial u}{\partial x} \right\|_{L^2(\mathbb{R})}^2$ and the total concentration $\|u\|_{L^2(\mathbb{R})}^2$. But we aren't able to conclude that each part of this difference is bounded. From (20) we conclude that the total concentration and the norm of the history of the gradient are bounded.

3. Numerical methods for the generalized FKPP equation

In this section we present simple first order numerical methods for solving the integro-differential equation (3). These methods are established from Proposition 1, that is by using finite difference discretizations of (5).

We consider a spatial uniform grid x_i such that $x_{i+1} - x_i = h$ and a uniform temporal grid t_n such that $t_{n+1} - t_n = k$. By u_j^n we denote a numerical approximation of $u(x_j, t_n)$.

Let us consider equation (5) at (x_j, t_n) . We consider numerical methods obtained by discretizing $\frac{\partial^2 u}{\partial t^2}(x_j, t_n)$ and $\frac{\partial u}{\partial t}(x_j, t_n)$ respectively with second order and backward finite difference operators.

3.1. An explicit method.

3.1.1. Convergence and qualitative behaviour. Let us consider the explicit Method $D_n R_n$ defined by

$$D_{2,t}u_j^n + D_{-t}u_j^n \left(\frac{1}{\tau} - f'(u_j^n) \right) = \frac{D}{\tau} D_{2,x}u_j^n + \frac{1}{\tau} f(u_j^n), \quad (21)$$

where

$$D_{-t}u_j^i = \frac{u_j^i - u_j^{i-1}}{k}, \quad D_{2,x}u_j^i = \frac{u_{j+1}^i - 2u_j^i + u_{j-1}^i}{h^2}, \quad D_{2,t}u_j^i = \frac{u_j^{i+1} - 2u_j^i + u_j^{i-1}}{k^2}.$$

To study the local stability in the neighborhood of the unstable steady state $u = 0$ (where $f'(0) > 0$) we use a von Neumann analysis in the linearized method. For a sake of simplicity let us assume that $\tau f'(0) = 1$. It can be shown that the amplification factor ξ satisfies

$$|\xi| \leq 1 + k f'(0) \quad (22)$$

provided that

$$\frac{Dk^2}{h^2\tau} \leq \frac{1}{2}, \quad (23)$$

and

$$k \leq \frac{1}{f'(0)^2}. \quad (24)$$

Numerical simulations obtained with Method $D_n R_n$ are shown in Figure 2 and Figure 3. The initial profile is an Heaviside function $H(x)$. The lack of stability of the method is well illustrated in Figure 3. We remark that while the data in Figure 2 verify (23), the data in Figure 3 violates this condition.

The diffusive behaviour of Method $D_n R_n$ can be understood by constructing the modified partial differential equation which exact solution is the numerical solution at the mesh nodes. If \bar{u} represents the interpolation function




FIGURE 2. Numerical solutions obtained by Method $D_n R_n$ - stable behaviour.




FIGURE 3. Numerical solutions obtained by Method $D_n R_n$ - unstable behaviour.

of u_j^n and assuming that this function is smooth enough then \bar{u} is a solution of

$$\frac{\partial^2 \bar{u}}{\partial t^2} \left(1 + \frac{k}{2} \frac{1 - \tau f'(0)}{\tau} \right) + \frac{\partial \bar{u}}{\partial t} \left(\frac{1 - \tau f'(0)}{\tau} - k \frac{f'(0)}{\tau} \right) = \frac{D}{\tau} \frac{\partial^2 \bar{u}}{\partial x^2} + \frac{f'(0)}{\tau} \bar{u}, \quad (25)$$

where second order terms have been discarded. If we consider the behaviour of a plane wave of form

$$\bar{u}(x, t) = e^{-p(m)t} e^{imx(x-q(m)t)} \quad (26)$$

when introduced in (25), we conclude that the parameter p , which measures diffusivity, is defined by

$$p(m) = -\frac{1 - f'(0)\tau}{2\tau + (1 - f'(0)\tau)k},$$

for m large enough. If the plane wave is introduced in the linearized version of (5) in the neighborhood of $u = 0$, p takes the value

$$p(m) = -\frac{1 - f'(0)\tau}{2\tau},$$

which means that the exact solution of the telegraph equation presents a smaller diffusivity than the numerical solution obtained with Method $D_n R_n$.

3.1.2. Velocity of propagation of traveling waves. The computation of the velocity of propagation of traveling waves is a central problem in diffusive reaction models. In this Section we study the velocities of numerical wave solutions obtained from Method $D_n R_n$. It is worthwhile to mention that even if we know that the solution of (3) evolves into a traveling wave of type $\psi(x - ct)$ – where c is the constant velocity of propagation – the solution of the equivalent telegraph equation

$$\psi''(c^2 - \frac{D}{\tau}) + c\psi'(\frac{1}{\tau} - f'(\psi)) - \frac{1}{\tau}f(\psi) = 0 \quad (27)$$

can not be computed from (27) because ψ and c are unknowns. However, using (27), we can proceed to a stability analysis of traveling wave solutions ψ , near $u = 0$. Solving the quadratic equation in δ ,

$$\delta^2(c^2\tau - D) + \delta(-c + f'(0)\tau c) - f'(0) = 0,$$

we obtain

$$\delta = \frac{c(1 - f'(0)\tau) \pm \sqrt{(1 - f'(0)\tau)^2 c^2 + 4(c^2\tau - D)f'(0)}}{2(c^2\tau - D)}.$$

To obtain a real solution ψ , with a physical meaning, we must have the radicand positive that is

$$c \geq \frac{\sqrt{4f'(0)D}}{1 + \tau f'(0)}.$$

To guarantee the stability of ψ we impose $1 - \tau f'(0) > 0$ and $c^2\tau - D < 0$.

To study the numerical speed we consider a family of functions of type

$$w_m(x, t) = a(m)e^{-mx + \lambda(m)t}, \quad (28)$$

with $m > 0$, and we prove in what follows that for a certain value of m the corresponding wave propagates with a velocity defined by (4). We recall that in [3] it has been proved that an Heaviside function also propagates with the same speed.

By replacing (28) in (27) with $f(u) = f'(0)u$ we conclude that (28) is a solution of

$$\frac{\partial^2 w}{\partial t^2} + \frac{\partial w}{\partial t} \left(\frac{1}{\tau} - f'(0) \right) = \frac{D}{\tau} \frac{\partial^2 w}{\partial x^2} + \frac{1}{\tau} f'(0) w \quad (29)$$

if and only if

$$\lambda^2 + \lambda \left(\frac{1}{\tau} - f'(0) \right) - \frac{1}{\tau} (m^2 + f'(0)) = 0. \quad (30)$$

The velocity $c(m)$, $c(m) = \frac{\lambda(m)}{m}$, is defined by

$$c_+(m) = \frac{-1 + \tau f'(0)}{2m\tau} + \sqrt{\frac{D}{\tau} + \frac{(1 + \tau f'(0))^2}{4\tau^2 m^2}} \quad (31)$$

and

$$c_-(m) = \frac{-1 + \tau f'(0)}{2m\tau} - \sqrt{\frac{D}{\tau} + \frac{(1 + \tau f'(0))^2}{4\tau^2 m^2}}. \quad (32)$$

As we want to characterize the traveling wave solutions connecting $u = 1$ with $u = 0$, we consider in what follows $c_+(m)$. We assume that $\tau f'(0) \leq 1$. It is a tedious but straightforward task to establish that



$$\min_{m>0} c_+(m) = c_+(m^*) = \frac{\sqrt{4Df'(0)}}{1 + \tau f'(0)}, \quad (33)$$

with $m^* = \sqrt{\frac{f'(0)}{D} \frac{1 + \tau f'(0)}{1 - \tau f'(0)}}$. In Figure 4 we plot the graph of $c_+(m)$ for $\tau = 0.5$, $f'(0) = 1$ and $D = 1$.

As proved before, to have a stable positive traveling wave $w_m(x, t)$ we should have

$$\frac{\sqrt{4f'(0)D}}{1 + \tau f'(0)} \leq c_+(m) \leq \sqrt{\frac{D}{\tau}}. \quad (34)$$

As $c_+(m^{**}) = \sqrt{\frac{D}{\tau}}$, with $m^{**} = \sqrt{\frac{\tau}{D} \frac{f'(0)}{1 - \tau f'(0)}}$, we conclude from (33) and (34), that w_m is stable and positive for $m \geq m^{**}$.

FIGURE 4. The graph of $c_+(m)$.FIGURE 5. Traveling waves for $u_0(x) = H(x)$ and $u_0(x) = e^{m^*(-x+c_+(m^*)t)}$.

We note that traveling waves (28) with velocity $c_+(m)$ for $m > 0$, define a family of solutions of the integro-differential modified problem

$$\begin{cases} \frac{\partial u}{\partial t} = \frac{D}{\tau} \int_0^t e^{-\frac{t-s}{\tau}} \frac{\partial^2 u}{\partial x^2}(x, s) ds + f'(0)u + (mv_+(m) - f'(0)) e^{-mx - \frac{t}{\tau}}, \\ (x, t) \in \mathbb{R} \times \mathbb{R}^+, \\ u(x, 0) = e^{-mx}, x \in \mathbb{R}, \end{cases} \quad (35)$$

which is equivalent to equation (29) with initial conditions

$$\begin{cases} \frac{\partial u}{\partial t}(x, 0) = mc_+(m)e^{-mx}, & x \in \mathbb{R}, \\ u(x, 0) = e^{-mx}, & x \in \mathbb{R}. \end{cases} \quad (36)$$

We have then constructed a family of trial functions such that, for each admissible velocity (34) there is an element of the family which propagates with this velocity.

In the following we use $c_+(m)$ to study the velocity of numerical traveling wave solutions computed with Method D_nR_n .

To compute the numerical velocity we replace u_j^n by a discrete traveling wave that is a discretization of (28), that is, $u_j^n = \xi^n e^{mjh}$, with $\xi = e^{c_n(m)k}$, where $c_n(m)$ represents the velocity of the numerical wave solution obtained by Method D_nR_n . We have

$$c_n(m) = \frac{1}{k} \ln \xi \quad (37)$$

where ξ is the solution of the following equation

$$\begin{aligned} \xi^2 + \xi \left(-2 + k \frac{1 - \tau f'(0)}{\tau} - k^2 \left(\frac{D e^{mh} + e^{-mh} - 2}{h^2} + \frac{f'(0)}{\tau} \right) \right) \\ + \left(1 - k \frac{1 - \tau f'(0)}{\tau} \right) = 0. \end{aligned} \quad (38)$$

After some computations we establish that

$$\xi = 1 + k \left(\frac{\tau f'(0) - 1}{2\tau} \pm \frac{1}{2} \sqrt{\frac{(1 + \tau f'(0))^2}{\tau^2} + 4 \frac{D}{\tau} m^2} + O(k) \right). \quad (39)$$

We have then proved the following result:

Proposition 3. *Let $c_+(m)$ and $c_n(m)$ represent the speed of traveling wave solutions respectively of the integro-differential equation (3) and of difference equation (21). Then*

$$c_n(m) = c_+(m) + O(k). \quad (40)$$

■

In Figure 6 we compare the numerical traveling wave solutions obtained with Method D_nR_n with the traveling wave defined by the Heaviside function and with the propagation speed $c_+(m^*)$.




FIGURE 6. Numerical traveling wave solutions computed with Method $D_n R_n$.

3.2. An implicit-explicit discretization.

3.2.1. Convergence and qualitative behaviour. The stability of Method $D_n R_n$ is achieved provided that the conditions (23), (24) are satisfied. These conditions are very severe if the reaction is stiff. In order to avoid these stability restrictions we consider in the following an implicit-explicit method - Method $D_{n+1} R_n$ - defined by

$$D_{2,t}u_j^{n+1} + D_{-t}u_j^n \left(\frac{1}{\tau} - f'(u_j^n) \right) = \frac{D}{\tau} D_{2,x}u_j^{n+1} + \frac{1}{\tau} f(u_j^n), \quad (41)$$

which has an amplification factor given by

$$|\xi| \leq 1 + \frac{f'(0)}{1 - k_0 f'(0)} k, \quad (42)$$

provided that

$$k < k_0 < \frac{1}{f'(0)}. \quad (43)$$

Numerical solutions obtained with Method $D_{n+1} R_n$ which show the better stability properties of this methods are plotted in Figure 7 and Figure 8.




FIGURE 7. Numerical solution obtained using Method $D_{n+1}R_n$ - stable behaviour.




FIGURE 8. Numerical solutions obtained using Methods $D_{n+1}R_n$ - oscillatory behaviour.

The solutions obtained with Method $D_{n+1}R_n$ present some oscillations (Figure 8). This wrong qualitative behaviour can be understood using again the modified equation approach. The modified equation associated with Method $D_{n+1}R_n$ is defined by

$$-\frac{D}{\tau}k \frac{\partial^3 \bar{u}}{\partial t \partial x^2} + \frac{\partial^2 \bar{u}}{\partial t^2} \left(1 + \frac{k}{2} \frac{1 - \tau f'(0)}{\tau} \right) + \frac{\partial \bar{u}}{\partial t} \frac{1 - \tau f'(0)}{\tau} = \frac{D}{\tau} \frac{\partial^2 \bar{u}}{\partial x^2} + \frac{f'(0)}{\tau} \bar{u}, \quad (44)$$

where second order terms have been discarded. It is easy to show that the parameter p , introduced in (26), is given by

$$p(m) = -\frac{1 - f'(0)\tau + \frac{Dk}{2}m^2}{2\tau + (1 - f'(0)\tau)k},$$

for m large enough. This expression enable us to conclude that the numerical solution obtained with Method $D_{n+1}R_n$ presents less diffusivity than the numerical solution obtained with Method D_nR_n .

3.2.2. Velocity of traveling waves. Proceeding as previously we can conclude that Proposition 3 holds for Method $D_{n+1}R_n$.

4. Conclusion

In the present paper we studied the behaviour of numerical traveling waves which are approximations to the solution of the integro-differential equation (3). We started by analyzing in Proposition 2 the well-posedness of the integro-differential model.

The numerical methods were constructed discretizing a partial differential equation equivalent to the integro differential equation (3). The equivalence between the two models was established in Proposition 1.

The first method considered was of explicit type – Method D_nR_n . This method is stable if the stepsizes satisfy conditions (23) and (24) which are very severe if stiff reactions are considered. This fact motivated the introduction of a method of implicit-explicit type – Method $D_{n+1}R_n$.

A central problem in the discrete integro-differential models is the velocity of propagation of the numerical traveling wave solutions. We established in Proposition 3 that the velocity of propagation of the numerical traveling wave solutions of Method D_nR_n is a first order approximation of its continuous counterpart. The same result holds for Method $D_{n+1}R_n$.

References

- [1] D.G. Aronson, H.F. Weinberger, 1978, Multidimensional nonlinear diffusion in population genetics, *Adv. Math.* 30,33-76.
- [2] J. Douglas, B.F. Jones Jr. 1962, Numerical methods for integro-differential equations of parabolic and hyperbolic type, *Numer. Math.* 4, 96-102.
- [3] S. Fedotov, 1998, Traveling waves in a reaction - diffusion system: diffusion with finite velocity and Kolmogorov-Petrovski-Piskunov kinetics, *Physical Review E* 5, 4, 5143-5145.
- [4] S. Fedotov, 1999, Nonuniform reaction rate distribution for the generalized Fisher equation: ignition ahead of the reaction front, *Physical Review E* 60, 4, 4958-4961.

- [5] S. Fedotov, 2001, Front propagation into an unstable state of reaction-transport systems, *Physical Review Letter* 86, 5, 926-929.
- [6] J. D. Murray, *Mathematical Biology-I,II: Spatial Models and Biomedical Applications*, 3 ed, 2003, Springer Verlag.
- [7] V. Mendez, J. Camacho, 1997, Dynamic and thermodynamics of delayed population growth, *Physical Review E* 55, 6, 6476-6482.
- [8] V. Mendez, J. Llebot, 1997, Hyperbolic reaction-diffusion equations for a forest fire model, *Physical Review E* 56, 6, 6557-6563.
- [9] V. Mendez, T. Pujol, J. Fort, 2002, Dispersal probability distributions and the wave front speed problem, *Physical Review E* 65, 041109.
- [10] I. H. Sloan, V. Thomée, 1986, Time discretization of an integro-differential equation of parabolic type, *SIAM J. Numer. Anal.* 23, 1052-1061.
- [11] N.-Y Zhang, 1993, On fully discrete Galerkin approximation for partial integro-differential equations of parabolic type, *Math. Comp.* 60, 201, 133-166.

A. ARAÚJO

DEPARTAMENTO DE MATEMÁTICA, UNIVERSIDADE DE COIMBRA, 3001 - 454 COIMBRA, PORTUGAL

E-mail address: alma@mat.uc.pt

J.A. FERREIRA

DEPARTAMENTO DE MATEMÁTICA, UNIVERSIDADE DE COIMBRA, 3001 - 454 COIMBRA, PORTUGAL

E-mail address: ferreira@mat.uc.pt

P. OLIVEIRA

DEPARTAMENTO DE MATEMÁTICA, UNIVERSIDADE DE COIMBRA, 3001 - 454 COIMBRA, PORTUGAL

E-mail address: poliveir@mat.uc.pt